

Ecomortar G

Consumption Chart

(Plastering)

Type G Mortar

Plaster Work	Pounds per square yard per 1/16" 5.07 lbs.	Pounds per square yard per 1/8" 9.93 lbs.
---------------------	--	---

European Calculations

Type G Mortar

Plaster Work	KGs per M ² @ 1mm deep 0.75 KGs	KGs per M ² @ 2mm deep 3.8 KGS
---------------------	--	---

Ecomortar G

Consumption Chart

(Masonry)

Type G Mortar

Pointing Brick Work (Standard Bricks)	Pounds per square yard at 3/8" deep 3.4 lbs	Pounds per square yard at 3/4" deep 7 lbs
Construction Brickwork single leaf _ brick thick	Pounds per square yard using a 2-1/2" x 4 x 8-1/4" brick (no frog) 32 lbs	Pounds per 100 square yards using a 2-1/2" x 4 x 8-1/4" brick (no frog) 3205 lbs
Construction Stone Masonry (Typically split faced walling)	Pounds per linear yard at 4" bed width x 3/8" thick 3.5 lbs	Pounds per linear yard at a 6" bed width x 3/8" thick 5.26 lbs

European Calculations

Type G Mortar

Pointing Brick work (Standard bricks)	KGs per M ² @ 10mm deep 1.85 KGs	KGs per M ² @ 20mm deep 3.8 KGS
Construction Brickwork single leaf _ brick thick	KGs per M ² using a standard 65mm X 103mm X 215mm brick (no frog) 17.4 KGs	KGs per 100 M ² using a standard 65mm X 103mm X 215mm brick (no frog) 1740 KGs
Construction Stone Masonry (Typically split faced walling)	KGs per linear M @ 100mm bed X 10mm thick 1.74 KGs	KGs per Linear M @ 150mm bed X 10mm thick 2.61 KGs